TWAL 6 ... 18 GHz
TWT Amplifiers

BONN Elektronik
YOUR ULTIMATE RF POWER SOURCE

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
TWAL 0618-300L	6 ... 18 GHz	300 / 320	54.8 / 60 ±5	6 / 10	3000	6 HU, 800 mm	47

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Noise Figure	20 dB max.
Class of Operation:	A-linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	WRD 650, standard on rear panel
Mains Supply:	100 ... 240 V AC ±10%, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... 45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	normal laboratory environment
Cooling:	forced air with integral blower air intake and exhaust at rear

OPTIONS

A) RF Monitor Outputs *)
B) External Dual Directional Coupler
C) IEEE-488.2 GPIB Remote Control
D) Front Panel RF Connectors
E) RF Power Indication (digital) *)
F) Gain Adjustment *)
G) Output Isolator *)
L) Remote Control
N) Harmonic Filter *)
R) RS-232C Remote Control
S) Internal RF Switching Unit *)
U) USB Remote Control
W) Liquid Cooling
X) External Control of other Amplifiers

*) These options may reduce output power and/or gain